

www.GRAVESPORT.com

Toll Free: 800-867-6480

Fax: 818-902-3821

7629 Densmore Avenue Van Nuys, Ca. 91406

FEK-16ZX1-K

Parts List:

Fender Eliminator Assembly

Fender Eliminator 2016 Kawasaki Ninja ZX-10R

<><< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>

- 1) Remove the passenger seat.
- Remove the four 4mm allen head bolts on the top of the rear tail section then carefully pull straight back and up to remove the rear tail section.
- 3) Locate the relay on the right side at the back of the tool kit tray (Photo 1) then slide it off its prong. Remove the four 8mm bolts (Photo 1). No need to remove completely. Just flip it back to gain access to the wiring underneath. On the left side, in the clear rubber wire cover, locate and unplug the 2 turn signal wires and the license plate light wire.




Photo 1

4) Remove the four 5mm allen head bolts (**Photo 2**) under the rear fender, holding it as it becomes loose. After the allen bolts have been removed, set the fender on the rear tire and carefully pull the wires through.



Photo 2

- The Graves Fender Eliminator is set up with turn signal mounts attached which accommodate the stock turn signals.
 - *** If you are using an integated taillight kit you can remove the turn signal brackets.

- 6) If you are using the stock turn signals, place the stock rear fender upside down on a work bench. Remove the two phillips head screws and the one 5mm allen head bolt to remove the wire cover. To remove the turn signals, remove the phillips head on the retaining plate. Take note of the order of the turn signal hardware. After all the turn signal hardware has been removed the turn signals will pop right out.
- 7) If the stock turn signals are being used on the Graves Fender Eliminator, re-install them in the reverse sequence. After the turn signals have been installed, feed the signal wires through the forward center hole of the Graves Fender Eliminator Mount.
- 8) Feed the signal wire back through the under tail of the motorcycle following the same path they came out. Using the stock fender allen bolts, install the Graves Fender Eliminator. Plug the turn signals back in
- Re-install the tool kit tray, bodywork and rear seat in reverse order.

