

www.GRAVESPORT.com

Toll Free: 800-867-6480

Fax: 818-902-3821

7629 Densmore Avenue Van Nuys, Ca. 91406

# PARTS LIST

## **Right Side**

 Right Frame Slider Assembly 60mm Hex Bolt 1 10mm Washer 1 Spacer - Short 1 Slider Puck 1

## Frame Sliders Yamaha R3 2015

## Left Side

- Left Frame Slider Assembly 100mm Hex Bolt
  - 10mm Washer Spacer . long Slider Puck

Mounting Bracket 1

## <<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>

## **RIGHT SIDE INSTALLATION**

- Remove the two (2) 4mm allen head screws located on the right side panel below the tank and seat. Carefully pull the side panel straight out. The panel will be held in place by 2 rubber grommets.
- 2) Remove the 4mm allen head screw located on the right lower side panel just above the motor mount on the head. Slide the panel forward with your left hand and pull out with your right hand to release the body clip. Then slide straight down to release the second body clip. **PHOTO 1.**

Remove the 10mm head bolt behind the panel. This will allow you to have flexibility with the side panels to install the Graves Frame Slider Mounting Bracket.





- **3)** Remove the three (3) 8mm allen head motor mount bolts. The stock motor mount will remain in place.
- 4) Using the three (3) 8mm stock allen head bolts without the washers, install the Graves Frame Slider Mounting Bracket. Torque the motor mount bolts to 49 ft. lb / 68 Nm.
- 5) Remove the rubber o-ring holding the right side frame slider assembly together. Apply a thread locking compound onto the threads of the bolt.
- 6) Install the right side Frame Slider Assembly into the Graves Mounting Bracket. Torque to 33 ft. lb / 45 Nm.
- 7) In reverse order, re-install the side panels.

### LEFT SIDE INSTALLATION

- 1) Remove the 8mm head motor mount bolt and washer going to the head.
- Remove the rubber o-ring holding the left side frame slider assembly together. Apply a thread locking compound onto the threads of the bolt.

1

1

1

 Install the left side Frame Slider Assembly to the stock motor mount and torque to 49 ft. Ib / 68 Nm.

### Note: Periodically check the torque of the bolts on the Frame Slider Assemblies.



EXY-15R3-CBSC

www.GRAVESPORT.com

The purchaser releases Graves Motorsports, Inc from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident. **This product is intended for Closed Course Competition Use Only** and may render the vehicle illegal for use on public roads.

Find us at: