

TOOL POUCH INSTALLATION INSTRUCTIONS

WARNING:

READ ALL INSTRUCTIONS THOROUGHLY BEFORE STARTING!

Use of this product in a manner other than its intended purpose could cause loss of motorcycle control and damage including personal injury or death. Follow the instructions below.

¥ You must mount bag properly and securely before riding motorcycle. Failure to do so could result in damage to the product and motorcycle.

¥ Tool bags must be tied down and secured to a solid part of the motorcycle to prevent any movement during operation.

¥ Do not exceed maximum weight of three pounds per tool bag.

¥ DO NOT ATTEMPT TO USE THIS TOOL BAG IF...

...you do not understand these instructions;

...you do not understand any part of the mounting system;

...you have any doubts as to the security of the mounting system.

¥ If you have any doubts or questions, SEEK PROFESSIONAL HELP at your qualified motorcycle dealer or call SADDLEMEN at 800-397-7709.

Motorcycling is an inherently dangerous activity. Installation of any accessory, including tool-bags, can add to the danger if they are not installed safely. You must install this product in a manner in which it will not contact any part of the drivetrain, suspension or steering, or interfere with any operation of the motorcycle. If you do not know how to do this, or have any doubts as to your ability, please have a qualified motorcycle mechanic install it.

PARTS LIST

- 1- Tool Pouch 2- Nylon straps 1- Instructions

INSTALLATION INSTRUCTIONS

1. Highwayman tool pouches are designed as a universal fit, using two straps to connect to just about anywhere on your motorcycle, i.e., triple clamp, sissybar, handlebars, luggage rack.
2. Two nylon mounting straps are included. Some applications will require use of both straps; for some applications one long strap will work best. Insert strap(s) into each of the square strap anchors located on the back of the bag. Straps can be inserted either vertically (for triple clamp or handlebar installation) or horizontally (for fork or sissybar installation). See Fig. A. Straps can also be cut to eliminate excess length.
3. See Fig. B for D-ring adjustment. Make sure to tighten both straps securely, and around a triple clamp or other part of the motorcycle so bag does not slide, or move around or come in contact with a tire or any moving part of the bike while riding.

DO NOT connect any straps to flexible or moving parts (rubber mounted turn signals, swingarm, shocks)

NOTE: You must tuck away or tie all loose mounting straps BEFORE you ride the motorcycle. See warning information above.

NOTE: Recheck strap tightness each time you stop riding.

CARE AND CLEANING

Your Highwayman Tool Pouch requires almost no maintenance, but to keep it looking good, here's what we recommend:

1. You can simply wipe down the bag with a clean, damp cloth, but to really make it shine, use a vinyl or leather cleaner/conditioner available at the hardware store or auto parts store.
2. Keep away from extreme heat sources like your bike's exhaust pipes.

SADDLEMEN'S ONE-YEAR WARRANTY

We guarantee our products for a period of one year after retail purchase, against defects in materials and workmanship. Damage caused by improper use or incorrect mounting is not warranted. Our warranty has other provisions and conditions; please contact Travelcade/Saddlemen for full details. If your Saddlemen product is not performing to your expectations, please call us directly and our customer service staff will be happy to help. You can count on Saddlemen's quality, innovation, service and style.

