

401 South Grand Ave., Santa Ana, CA 92705 Tel: 714.550.6070 Fax: 714.550.9661 www.twobros.com



2009 Can-am **Outlander MAX 800R**

V.A.L.E.™ Slip-on Exhaust System with M-7 Aluminum Canister Part # 005-2550406V



Parts List

Qty.	Description	Part Number
1	Muffler Canister M-7 Aluminum	005-255-206M
1	Stainless Steel S-Bend Slip-On	005-25504S
1	HARDWARE KIT	005-227-3C
1	X-Ring	005-7-2-2
1	Muffler bracket	005-255B
2	8mm Flange nut	005-FN8
1	8x25mm Socket Head Cap Screw	005-SH825
1	8x60mm Socket Head Cap Screw	005-SH860
1	61mm Barrel Clamp	005-27-61MSH
1	5mm Long Handle Ball end hex key	005-9-18610
1	T20Torx Screw Wrench	005-9-15820
4	M6 Split Lock Washer	005-WL6
4	6x14mm Socket Head Cap Screw	005-SH614
1	TBR Sticker Kit	015-10212

IMPORTANT - PLEASE READ CAREFULLY

We recommend that this performance part be installed by a qualified technician. If you have any doubts as to your ability to install this performance part, please consult with your local ATV dealer. Read all instructions first before starting installation. Make sure the ATV and exhaust system are completely cool before starting the installation. Also, make sure the ATV is secure on a level surface and the wheels are chocked to prevent the ATV from rolling during installation. Be sure to save all stock components for possible use later.

Warranty

Two Brothers Racing products are intended for closed course competition purposes only, and therefore are sold "as is" without warranty. Two Brothers Racing specifically disclaims any warranties of merchantability or fitness for a particular purpose and disclaims all responsibility for consequential and incidental damages or any other losses arising from the use of these products or parts.

- Make sure the ATV is completely cool before starting 7.
- 1. the installation. Make sure the ATV is secure on a level surface and the parking brake is tset.
- 2. Remove passenger seat assembly.



3. Remove main seat and rear cover.



Remove left side engine panel. 4.



Remove heat shield. 5.



6. Loosen muffler joint clamp.



Remove muffler assembly.

Installation Instructions



Attach slip-on tube to TBR muffler using the provided 4 8. 6x14mm bolts and lock washers with X-ring. Leave loose for now.



Attach muffler mounting bracket (supplied) to rear OEM 9. muffler mounting hole using the supplied 8x60mm bolt and nut. Slide barrel clamp on end of slip tube.



10. Install muffler assembly and attach to mounting bracket using the 8x25mm bolts and nuts provided.



- Tighten the X-ring bolts. 11.
- 12. Tighten Barrel clamp.
- 13. Re-install heat shield, side panel and seats.
- 14. Double check your work and make sure all bolts are tightened and the exhaust is aligned correctly.
- 15. Before you run the ATV, clean off all fingerprints and dirt, as any oily residue will etch the metal and become somewhat permanent when the system gets hot. Run the ATV and enjoy. It is normal for some white smoke to appear the first time you start the ATV. This is packing/ manufacturing oil from inside the pipe burning off. Check for gaps or leaks. If you find a leak, a little high temperature silicon sealant should fix it. After 50 to 100 miles, recheck all fasteners for tightness.



Brushed Aluminum Canisters: Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth.

Carbon Fiber Canisters: Clean using a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth, Always make sure the fiberglass packing inside is in good condition and not burned out, as exhaust heat inside an empty canister will deteriorate the carbon fiber sleeve. TBR sells repack kits (Road - #005-10038, Offroad - #005-10038MX) that include everything you need to easily do it yourself.

Titanium Mufflers: For cleaning use a mild water based spray cleaner. Always apply cleaner or polish with a soft, clean cloth. Always make sure the fiberglass packing inside is in good condition and not burned out, as exhaust heat inside an empty canister will deteriorate the carbon fiber sleeve. TBR sells repack kits (Road - #005-10038, Offroad - #005-10038MX) that include everything you need to easily do it yourself.

Repack all road canisters every 3,000 miles. Part #005-10038 Repack all offroad canisters after every 10 hours of use. Part #005-10038MX

Stainless Steel S-Bend Slip-On

8x25mm Socket Head Cap Screw

8x60mm Socket Head Cap Screw

6x14mm Socket Head Cap Screw

5mm Long Handle Ball end hex key

HARDWARE KIT

Muffler bracket

8mm Flange nut

61mm Barrel Clamp

T20Torx Screw Wrench

M6 Split Lock Washer

TBR Sticker Kit

X-Ring

005-25504S

005-227-3C

005-7-2-2

005-255B

005-SH825

005-SH860

005-27-61MSH

005-9-18610

005-9-15820

005-WL6

005-SH614

015-10212

005-FN8

NEVER dyno test your bike with carbon fiber or titanium canisters installed - the intense heat and lack of cooling air can quickly burn through the canister material. Two Brothers Racing does not provide a warranty for burned canisters.