



Yamaha R6 06-13

Fender Eliminator Kit Contents

Description	Quantity	Description	Quantity
Fender Brackets	1	6mm Locknut	8
6x25 Bolt	4	6x15mm Washer	8
6x12 Bolt	4	6x12mm Washer	2

- · Remove Rider Seat and Rear Seat.
- Remove rear upper tail bodywork.
- Remove rear seat latch, by removing cotter pin and (2) 6mm button heads bolts.
- Remove aluminum seat support; by removing (8) 6mm button head bolts.
- Disconnect marker light wires and tail light wires.
- Lift up trunk tray.
- Remove (4) fender bolts.
- Carefully slider marker lights through hole as you pull down on fender.
- Loosely install right and left VORTEX Fender Eliminator Brackets using supplied (4) 6 x 25mm bolts washers and locknuts.
- Loosely install license plate bracket using supplied (2) 6 x 12mm button head bolts, washers and locknut.
- With license plate bracket centered, tighten all nuts and bolts.
- Install marker lights and license plate.
- Reconnect marker light wires, brake light wires and plate light wires (not included).
- Check light for proper function.
- Mount rear upper tail bodywork.
- Mount seats.
- Remaining hardware to be used for mounting license plate

Use blue thread locker to secure bolts. Refer to owner's manual for proper torques.